



Pro-Lift: Treatment 680

This versatile three-section table is ideal for physiotherapy, massage, beauty treatments, examinations or any multimodality practice. The 680mm backrest configuration allows for more legroom when seated compared to the Treatment 930.

SELECT FROM OVER 30 COLOURS AND FABRIC CHOICES INCLUDING POLYURETHANE (PU), VINYL (PVC) AND GENUINE ITALIAN LEATHER:



PRODUCT INFORMATION



MANUALLY ADJUSTABLE BACKREST

The lift-up back adjusts in seconds to create a sturdy, comfortable treatment platform – an ideal choice for massage, beauty treatments, examinations or any multimodality practice.



ADJUSTABLE HEAD SECTION

The standard configuration includes a face hole in the head section for more comfortable prone treatments. The head section can be finely adjusted to enable the prone patient to relax the neck muscles fully during treatments.





FACE HOLE OPTIONS

Choose a face recess in the lift-up back or head section. Order a face hole plug to help move patients quickly between prone and supine positions – no need to rotate the patient to avoid the face hole.











FOAM OPTIONS

Choose between five Dunlop® cushioning systems ranging from Ultra Firm to luxurious Viscoflex® slow release memory foam. We have the right foam system to suit your modality.

TABLE WIDTH

Select from three table widths to suit your modality. Custom width tabletops are also available at an additional cost.

BASE STYLE

Choose between our Standard base with concealed in-line wheels and floor-levelling feet or our lockable Castor base for easy manoeuvrability. All wheels feature TPE rubber compound tread to protect your floors.

KEY OPTIONS

	STANDARD		OPTIONAL	
DUNLOP CUSHIONING	55mm, medium finish		Enduro (70mm, firm finish)	
			Luxura (80mm, luxurious finish)	
			Firm (50mm, firm finish)	
			Ultra Firm (50mm, very firm finish)	
BACKREST	Manually adjustable		N/A	
HEAD SECTION	Manually adjustable		N/A	
FACE HOLE	In the head section		In the backrest	No face hole
FACE HOLE PLUG	No face hole plug		Optional	
BASE STYLE	Concealed in-line wheels		75mm locking castors	
FOOTSWITCH	Single		One on each side of the table	
TABLE WIDTH	610mm	660mm	710mm	

KEY SPECIFICATIONS

ADJUSTMENTS	Backrest: +65° Head section: +40° to -75°	
SAFE WORKING LOAD	220kg	
MOTOR	Lift force: 10,000N Speed: 37mm/sec Height adjustment (min to max): 487mm in 13 seconds Speed test load: 180kg	
FOOTSWITCH	Ergonomic low profile design (20mm) Stainless steel Pneumatic control	
SHIPPING	1930 x 730 x 720mm 125kg	
WARRANTY	Structural: 15 years Hardware: 5 years Motor: 3 years Footswitch: 1 year Upholstery: To arrive in perfect condition	



